

# USB-SA124B Spectrum Analyzer and Measuring Receiver

100 kHz to 12.4 GHz



---

The perfect tool for general field and lab use, electrical engineering students, ham radio enthusiasts, and electronic hobbyists alike

---

Write automated testing and/or data collection applications with included API that is Windows®-based and Matlab®/LabVIEW® compatible

---

---

Use as a down-converter with a 63 MHz IF Output and a 6 MHz Resolution Bandwidth

---

Use over the entire 0°C to +50°C Operating Temperature Range with full accuracy

---

---

Now with real-time mode for spans of 250 kHz or less

---

# USB-SA124B Spectrum Analyzer and Measuring Receiver

6 March 2015

## FREQUENCY

- Frequency Range: 100 kHz to 12.4 GHz
- Timebase: 10 MHz reference in and out
- Internal Frequency Reference Accuracy:  $\pm 1$  ppm (standard);  $1 \times 10^{-7}$  (option-02)
- Resolution Bandwidth: 1 Hz to 250 kHz and 6 MHz

## AMPLITUDE (RBW $\leq 100$ KHZ)

- Range: +10 dBm to Displayed Average Noise Level (DANL)
- Absolute Accuracy (0dB to DANL):  
 $\pm 1.5$  dB (100 kHz to 6 GHz)  
 $\pm 2.5$  dB (6 GHz to 12.4 GHz)

## DISPLAYED AVERAGE NOISE LEVEL (DBM/HZ)

100 kHz to 10 MHz	-147 dBm
10 MHz to 100 MHz	-151 dBm
100 MHz to 3.0 GHz	-152 dBm
3.0 GHz to 5.5 GHz	-145 dBm
5.5 GHz to 7.0 GHz	-149 dBm
7.0 GHz to 8.0 GHz	-147 dBm
8.0 GHz to 11.0 GHz	-134 dBm
11.0 GHz to 12.4 GHz	-129 dBm

## RESIDUAL RESPONSES (RBW = 6.5KHZ)

100 kHz to 10 MHz	-100 dBm
10 MHz to 8.0 GHz	-93 dBm
8.0 GHz to 11.0 GHz	-82 dBm
11.0 GHz to 12.4 GHz	-85 dBm

## SSB PHASE NOISE AT 10 GHZ (TYPICAL)

Frequency Offset	dBc/Hz
100 Hz	-72
1 kHz	-80
10 kHz	-87
100 kHz	-87
1 MHz	-110

## IF OUTPUT

- 63 MHz with 6 MHz bandwidth for down conversion of NTSC, PAL, SECAM, ATSC, and DTV formatted signals

**CALIBRATION INTERVAL** 1-year



## MEASURING RECEIVER (TYPICAL AFTER 30 MIN WARM-UP AND $\pm 3^{\circ}\text{C}$ OF REF. START TEMP.)


- Operating Frequency: 100 kHz to 12.4 GHz
- Modulation Measurement Accuracy:  $\pm 1\%$  for AM & FM
- Synchronous Level Detector  
 $\pm 0.25$  dBc (0 dBm to -127 dBm, 100 kHz to 1.0 GHz)  
 $\pm 0.25$  dBc (0 dBm to -117 dBm, 1.0 GHz to 6.0 GHz)  
 $\pm 0.25$  dBc (0 dBm to -102 dBm, 6.0 GHz to 12.4 GHz)

## SPIKE™ SOFTWARE

Signal Hound's Spike™ software allows the SA124B to function as a real-time spectrum analyzer (RTSA), using its real-time mode, for sweeps of 250 kHz and less—that means every RF event will be captured when using spans that are  $\leq 250$  kHz. Graphics include color persistence and a 2D waterfall display.

## OPERATING TEMPERATURE

- $0^{\circ}\text{C}$  to  $+50^{\circ}\text{C}$  with full accuracy



## SYSTEM REQUIREMENTS

Signal Hound's Spike™ software is compatible with Windows® 7, 8, and 10 operating systems. You must have at least 200MB of free disc space, 4GB of RAM, two adjacent USB 2.0 ports, and a minimum of an Intel® Atom™ N2600 or Intel® Core™ i3 processor.