



STE3300F2



**Key Features:**

Included Interface Options

STEUSB2071

Included Power

6 Outlet 120VAC Power Strip

Included Ventilation

None

I/O Plates Included

1

Loading Style

TOP

Warranty

1 YEAR

Category

FORENSIC

Absorber/foam

3/4" INSERTION LOSS

External Dimensions

21.1"(W) X 13.2"(D) X 9.7"(H)

Internal Dimensions

**For more info, contact us:**

[Rotema@mtisummit.co.il](mailto:Rotema@mtisummit.co.il)

Mobile: +972-54-3181903

Office: +972-3-9008900 / 506



16.2"(W) X 10.2"(D) X 7.5"(H) Shipping  
Dimensions  
30"(W) X 23"(D) X 19"(H)  
Approx. Shipping Weight  
28lbs  
Shielding Effectiveness (dB)  
Isolation At 2.4GHz  
>95dB  
Isolation At 5.8GHz  
>90dB

**INCLUDES THE FOLLOWING STANDARD ITEMS:**

- RF isolated 6-outlet 110VAC power strip
- RF isolated 6-pole feed-through terminal block
- RF isolated USB2.0 high speed interface

The STE3300F2 was designed to give the forensics technician the equivalent of a highly isolated screen room right on his bench to perform electronic device interrogations. The smart phone is now a communications command console that incorporates email, text and SMS messages, document storage, picture, image, and media storage, notepad, journal, and a host of other functions and services. And each of those services has a history that is critical to access during a device interrogation.

The RF filtered AC power interface as well as the USB2.0 interface are located on the spacious universal removable I/O panel. This leaves plenty of room for a host of other I/O options that you may need to suit your specific test applications. From international power options to virtually every data and RF interconnect, we have the option available that you require.

The STE3300F2 is designed around the same heavy duty, rugged .090" and .125" aluminum used throughout all of our enclosures. It also features our custom engineered GEN-2 RF gaskets. With over a year in the R&D lab, these new gaskets provide a previously unheard of and flawless RF seal while being immune to the fixed compression set of typical stainless gaskets. Likewise, the STE3300F2 also features our GEN-2 RF absorbent and reflective foam lining. This foam was designed from the ground up, to our demanding specifications to provide maximum performance over all operating frequencies and bands.

Tamper-proof hardware and dual padlock latches prohibit unauthorized access and maintains the chain of custody for the devices collected.

**For more info, contact us:**

[Rotema@mtisummit.co.il](mailto:Rotema@mtisummit.co.il)

Mobile: +972-54-3181903

Office: +972-3-9008900 / 506



- Designed for lab and bench visual forensics interrogations
- 1/2" GEN-2 high efficiency RF foam liner
- GEN-2 high efficiency RF gaskets
- Exclusive double lip RF seal
- Universal removable I/O panel

#### Isolation

- >95dB @ 2.4GHz
- >90dB @ 5.8GHz

**For more info, contact us:**

[Rotema@mtisummit.co.il](mailto:Rotema@mtisummit.co.il)

Mobile: +972-54-3181903

Office: +972-3-9008900 / 506

