



STE4500



Key Features:

Included Interface Options

None

Included Power

6 Outlet 120VAC Power Strip

Included Ventilation

120MM Honeycomb Vents

I/O Plates Included

3

Loading Style

TOP

Warranty

1 YEAR

Category

BENCH TOP

For more info, contact us:

Rotema@mtisummit.co.il

Mobile: +972-54-3181903

Office: +972-3-9008900 / 506



Absorber/foam
3/4" INSERTION LOSS External
Dimensions
25.5"(W) X 16.4"(D) X 19.6"(H)
Internal Dimensions
20.7"(W) X 13.7"(D) X 17.2"(H)
Shipping Dimensions
33"(W) X 24"(D) X 21"(H)
Approx. Shipping Weight
55lbs
Shielding Effectiveness (dB)
Isolation At 2.4GHz
>85dB
Isolation At 5.8GHz
>85dB

INCLUDES THE FOLLOWING FEATURES:

- 6 Outlet 120VAC Power Strip
- 6 Pole Filtered Terminal Block feedthrough
- RF tight viewing window
- (2) ULTRA HIGH ISOLATION FLEXIBLE GLOVES GEN-3

- Designed for a wide variety of RF testing, function/s determined by user customization.
- Perfect for (Wi-Fi 4, 5, 6, 6E (802.11a/b/g/n/ac/ax)
- Wireless device testing
- Bluetooth, RFID, 3G, 4G, 5G testing
- Totally customizable with a wide variety of I/O options available

The popularity of the STE4400's larger size along with the patented hands-on manipulability of the STE3000B brought you the STE4500! The exclusive RF tight hands-on silver mesh gloves and illuminated viewing window are integral to the large 22.5"W x 18" H wide front of the enclosure. Dual gas filled struts hold the hinged top open for easy access for the largest devices, including laptops! Like other STE series enclosures, a universal stainless steel I/O connector interface plate is used to provide you with any combinations of "custom" milled connectors and I/O's that you may require.

Features:

- Designed for WLAN testing

For more info, contact us:

Rotema@mtisummit.co.il

Mobile: +972-54-3181903

Office: +972-3-9008900 / 506



- Top loading swing away door
- Exclusive double lip RF tight gasket
- Universal I/O connector interface plate
- Insertion Loss RF absorbent foam liner Standard
- Reflection Loss solutions available
- Optional security locking latch available

Isolation (**Base Enclosure**, may vary depending on I/O or options selected in final configuration):

- >85dB To 2.4GHz
- >85dB To 5.8GHz

I/O Connectors:

- See options for off the shelf connectors/interfaces available.
- Coaxial connectors: SMA, BNC, TNC, N, N to SMA, etc..
- Digital interfaces: USB, Ethernet, Video, Serial, Audio, Fiber, etc..
- Power filter interface: AC and DC
- Power Strip Options: US, UK, European, France, Swiss, Italy, Israel, India, China, Australia, Multi Country Config, etc...
- Custom connection options can be sourced through our Engineering Team.

For more info, contact us:

Rotema@mtisummit.co.il

Mobile: +972-54-3181903

Office: +972-3-9008900 / 506

